



COFFEE MACHINE WITH E61 TYPE GROUP AND MANUAL CONTROL OF THE WATER FLOW. THE DUAL BOILER ENSURES AN EXCELLENT THERMAL STABILITY. IT IS DESIGNED FOR THE REAL HOME BARISTA THAT WANTS HOW TO GET THE BEST FROM EACH COFFEE.

### TECHNICAL FEATURES

- E61 type group, paddle system with patented design, compatible with LELIT58 barista tools
- Professional water/steam taps with spring closure
- LCC with high-resolution OLED graphic display
- Lack of water in the tank and "Reserve mode" graphic indicator
- Possibility to activate pre-infusion and stand-by times
- Possibility of disabling the steam boiler
- Partial and total doses counter
- Coffee delivery timer
- Temperature displayed in Celsius or Fahrenheit degrees
- Double manometer for pump/steam pressure
- E61 type group manometer for coffee pressure
- Water supply and direct discharge
- Pump calibration via external adjustment screw
- Polished stainless steel appliance body with cup warmer rack and drip tray with wire grate
- Walnut wood knobs, lever, paddle and feet
- I/O stainless steel back-lit switch
- Anti-burn multidirectional steam and hot water wands
- Mug friendly
- Water tank placeable on the three sides of the machine

Stainless steel steam boiler: 1.5 l

Stainless steel coffee boiler: 800 ml

Water tank: 2.5 l

Dimensions LxDxH: 29x48.5x40 cm

Weight: 26.5 kg

### DELIVERED WITH

- LELIT58 bottomless filterholder with walnut wooden handle
- LELIT58 2-ways filterholder with walnut wooden handle and Coffee Slide spout
- LELIT58 1 dose filter (9-11 g), IMS
- LELIT58 2 doses filter (14-18 g), IMS
- LELIT58 2 doses PLUS (18-21 g), IMS
- LELIT58 blind filter, IMS
- LELIT58 stainless steel tamper with aluminium handle
- Spoon for coffee powder
- Cup rack
- 70 l water softener filter
- Small brush with nylon bristles
- LELIT microfiber cloth
- Optional 4-holes steam wand nozzle

PL162T 230 V 50 Hz | Plug Type E+F

PL162T-AUS 240 V 50 Hz | Plug Type I

PL162T-120 120 V 60 Hz | Plug Type B

PL162T-100 100 V 50/60 Hz | Plug Type B

