

PL92T



THE DUAL BOILER AND THE LELIT58 COMMERCIAL GROUP ARE ELIZABETH'S SPECIAL FEATURES AND ENSURE A CONTINUOUS STEAM DELIVERY AND THE EXTRACTION OF A CONSIDERABLE QUANTITY OF WATER, WITHOUT INFLUENCING COFFEE PERFORMANCE. THE ACCURATE CHOICE OF MATERIALS AND ITS DETAILS MAKE IT A WONDERFUL PIECE OF DESIGN EVEN WHEN THE MACHINE IS TURNED OFF.

TECHNICAL FEATURES

LELIT58 commercial group compatible with LELIT58 barista tools

3 ways solenoid valve to dry up the coffee puck

LCC with high-resolution OLED graphic display

Graphic indicator for lack of water in the tank and "Reserve mode"

Possibility to activate the automatic purge, the preinfusion, the stand-by and the washing cycle

Possibility to disable the steam boiler

Temperature of coffee, water and steam indicated in Celsius or Fahrenheit degrees

Back-lit manometer for coffee pressure

Brushed stainless steel appliance body with drip tray and wire grate

Wide cup warmer

Back-lit stainless steel buttons

Multidirectional anti-burn steam wand and fixed hot water wand

Mug friendly

Brass coffee boiler: 300 ml

AISI316L stainless steel steam/hot water boiler: 600 ml

Water tank: 2.5 l

Dimensions LxDxH: 31x27x38 cm

Weight: 12 kg

DELIVERED WITH

LELIT58 2-ways filterholder with design handle and Coffee Slide spout

LELIT58 1 dose filter (7-9 g)

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 blind filter, IMS

Tamper

Spoon for coffee powder

35 l water softener filter

Cup rack

First cleaning kit

PL92T 230 V 50 Hz | Plug Type E+F

PL92T-AUS 240 V 50 Hz | Plug Type I

PL92T-AS 220 V 50/60 Hz | Plug Type G

PL92T-120 120 V 60 Hz | Plug Type B

