

## PL62X



COFFEE MACHINE WITH E61 TYPE GROUP AND AUTOMATIC CONTROL OF THE EXTRACTION TEMPERATURE. THE PERFECT COFFEE AT THE RIGHT TEMPERATURE IN JUST 24 MINUTES, STABLE THERMAL EQUILIBRIUM WITH ANY COFFEE BLEND.

### TECHNICAL FEATURES

- E61 type group with mechanical pre-infusion compatible with LELIT58 barista tools
- Double probe HX System with thermosyphonic circulation (Patent pending)
- Silent pump
- Temperature configuration button (Warm - Hot - Extra Hot)
- Mode setting button (Classic HX mode or X mode)
- Professional water-steam taps with spring closure
- Machine ready and/or warming-up LED
- Lack of water in the tank or no-tank LED
- Active "Reserve mode"
- I/O stainless steel back-lit switch
- Double manometer for pump/steam pressure
- Brushed stainless steel appliance body with cup warmer rack and drip tray with wire grate
- Anti-burn multidirectional steam and hot water wands
- Mug friendly
- Adjustable feet

Boiler: 1.8 l with AISI316L stainless steel heat-exchanger

Water tank: 2.5 l

Dimensions LxDxH: 22x41x35 cm

Weight: 18.8 kg

### DELIVERED WITH

- LELIT58 2-ways filterholder with classic polished black handle and Coffee Slide spout
- LELIT58 1 dose filter (9-11 g), IMS
- LELIT58 2 doses filter (14-18 g), IMS
- LELIT58 2 doses PLUS filter (18-21 g), IMS
- LELIT58 blind filter, IMS
- LELIT58 stainless steel tamper with red wooden handle
- Spoon for coffee powder
- Cup rack
- 35 l water softener filter
- First cleaning kit
- Small brush with nylon bristles

PL62X 230 V 50 Hz | Plug Type E+F

PL62X-AUS 240 V 50 Hz | Plug Type I

PL62X-AS 220 V 50/60 Hz | Plug Type G

PL62X-100 100 V 50/60 Hz | Plug Type B

PL62X-120 120 V 60 Hz | Plug Type B

